



Type A: Externally Toothed T

Type B: Internally Toothed

Type C: Countersunk

Material: Carbon Spring Steel
Hardness: 42 to 49 HRC

Finish: Phosphating or as per requirements

Nominal Size d1 H13	d2(h14)	d3	s1	s2	Number of Teeth Min Types		Suitable Screw Size
					A and B	C	
					1.7	3.6	
(1.9)	4	-	0.3	-	6	-	M1.8
2.2	4.5	4.2	0.3	0.2	6	6	M2
2.7	5.5	5.1	0.4	0.2	6	6	M2.6
3.2	6	6	0.4	0.2	6	6	M3
(3.7)	7	7	0.5	0.25	6	6	M3.5
4.3	8	8	0.5	0.25	8	8	M4
5.1	9	-	0.5	-	8	-	M5
5.3	10	9.8	0.6	0.3	8	8	M5
6.4	11	11.8	0.7	0.34	8	10	M6
(7.4)	12.5	-	0.8	-	8	-	M7
8.2	14	-	0.8	-	8	-	M8
8.4	15	15.3	0.8	0.4	8	10	M8
10.5	18	19	0.9	0.5	9	10	M10
12.5	20.5	23	1	0.5	10	10	M12
(14.5)	24	26.2	1	0.6	10	12	M14
16.5	26	30.2	1.2	0.6	12	12	M15
(19)	30	-	1.4	-	12	-	M18
21	33	-	1.4	-	12	-	M20
(23)	36	-	1.5	-	14	-	M22
25	38	-	1.5	-	14	-	M24
(28)	44	-	1.6	-	14	-	M27
31	48	-	1.6	-	14	-	M30